

## Luminaire

Code AQ74304APP  
Name A.24 SOSP SA360 1122 SHRP FL4000 BK APP\*

## Measur.

Code FTS2000036  
Name A.24 SOSP SA360 1122 SHRP FL4000 BK APP\*

Luminaire Flux	3484.74 lm	Luminaire Power	42.00 W	Efficacy	82.97 lm/W	Efficiency	100.00%
Lamps Flux	3484.74 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Round Luminaire Round Luminous Area		Diam.	1122 mm	Height	54 mm		
		Diam.	88 mm	Height	0 mm		
Horizontal Luminous Area	0.006082 m2			Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°	0.001471 m2		
Coordinate system	CG			Symmetry Type	Double Symmetrical		
Date	21-11-2018			Maximum Gamma Angle	180		
Measurement Distance	0.00			Measurement Flux	3484.74 lm		
LED Flux=4281lm LED Power=38W Eff=81% EfcLed=113lm/W EfcLum=83lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	98 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		



