

Luminaire

Code AQ75301APP
Name A.24 SOSP SA360 1500 SHRP FL4000 WH APP*

Measurem.

Code FTS2000073
Name A.24 SOSP SA360 1500 SHRP FL4000 WH APP*

Luminaire Flux	6969.48 lm	Luminaire Power	83.00 W	Efficacy	83.97 lm/W	Efficiency	100.00%
Lamps Flux	6969.48 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Round Luminaire Round Luminous Area	Diam. 1550 mm Diam. 124 mm	Height	54 mm	Height	0 mm		
Horizontal Luminous Area	0.012076 m2	Emitting area on Plane 180°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002922 m2		
Coordinate system	CG	Symmetry Type	Double Symmetrical				
Date	21-11-2018	Maximum Gamma Angle	180				
Measurement Distance	0.00	Measurement Flux	6969.48 lm				
LED Flux=8562lm LED Power=76W Eff=81% EfcLed=113lm/W EfcLum=84lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	98 100 100 100 100	D DIN 5040	A60				
F UTE	--	B NBN	BZ 1				



