

## Luminaire

Code AQ37304+AQ16XXX  
 Name A.24 PLAF. MOD. DIFF. 90° PERP 2700K BLK + A.24 SCHERMO DIFF. OPALINO

## Measurerm.

Code FTS2300218  
 Name A.24 PLAF. MOD. DIFF. 90° PERP 2700K BLK + A.24 SCHERMO DIFF. OPALINO

Luminaire Flux	1340 lm	Luminaire Power	14.0 W	Efficacy	95.714 lm/W	Efficiency	100.00%
Source Flux	1340 lm	Maximum value	261.89 cd/klm	Position	C=90.00 G=45.00	CG	Sym. on planes 270-90
Rectangular Luminaire		Length	330 mm	Width	27 mm	Height	330 mm
Rectangular Luminous Area		Length	330 mm	Width	24 mm	Height	0 mm
Horizontal Luminous Area		0.007920 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.001916 m <sup>2</sup>	
Coordinate system		CG Roads		Symmetry Type		Sym. on planes 270-90	
Date		20-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1340 lm	

LED Flux=2346lm LED Power=13W Eff=57% EfcLed=176lm/W EfcLum=96lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(17k)=102000h

C.I.E. 36 65 86 77 100

D DIN 5040

B21

