

## Luminaire

Code AQ44115  
Name A.24 SOSP.MOD.D.SHARP4000K XF 1176 BSV

## Measurement

Code FTS1802269  
Name A.24 SOSP.MOD.D.SHARP4000K XF 1176 BSV

Luminaire Flux	1852 lm	Luminaire Power	22.0 W	Efficacy	84.190 lm/W	Efficiency	100.00%
Source Flux	1852 lm	Maximum value	1052.56 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire	Length	1175 mm	Width	27 mm	Height	55 mm	
Rectangular Luminous Area	Length	258 mm	Width	12 mm	Height	0 mm	
Horizontal Luminous Area	0.003096 m2	Emitting area on Plane 180°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2	Emitting area on Plane 90°	0.000749 m2
Emitting area on Plane 0°	0.000000 m2	Glare area at 76°					
Emitting area on Plane 90°	0.000000 m2						
Coordinate system	CG	Symmetry Type	Double Symmetrical				
Date	21-11-2018	Maximum Gamma Angle	180				
Measurement Distance	0.00	Measurement Flux	1852 lm				
LED Flux=2140,5lm LED Power=20W Eff=87% EfcLed=107lm/W EfcLum=84lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	98 100 100 100 100	D DIN 5040	A60				
F UTE	--	B NBN	BZ 1				

1175mm x 27mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 0.00 %  
DLOR 100.00 %  
RN 0.00 %



