

## Luminaire

Code AQ21001  
Name A.24 INCAS. MODULO SHARP 3000K FL 1176mm WHT

## Measurement

Code FTS1802185  
Name A.24 INCAS. MODULO SHARP 3000K FL 1176mm WHT

Luminaire Flux	1628 lm	Luminaire Power	22.0 W	Efficacy	74.004 lm/W	Efficiency	100.00%
Source Flux	1628 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1176 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	258 mm	Width	12 mm	Height	0 mm
Horizontal Luminous Area		0.003096 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.000749 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1628 lm	
LED Flux=2000,1lm LED Power=20W Eff=81% EfcLed=100lm/W EfcLum=74lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	98	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



