

## Luminaire

Code AQ21401  
Name A.24 INC.MOD.SHARP 2700K FL 1176mm WHT

## Measurement

Code FTS1802173-A  
Name A.24 INC.MOD.SHARP 2700K FL 1176mm WHT

Luminaire Flux	1617 lm	Luminaire Power	22.0 W	Efficacy	73.482 lm/W	Efficiency	100.00%
Source Flux	1617 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1176 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	258 mm	Width	12 mm	Height	0 mm
Horizontal Luminous Area		0.003096 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.000749 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		17-11-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1617 lm	

LED Flux=1986lm LED Power=20W Eff=81% EfcLed=99lm/W EfcLum=73lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=272160h

C.I.E. 98 100 100 100 100  
F UTE --

D DIN 5040  
B NBN

A60  
BZ 1



