


Luminaire

Code BH26401+BH16204
 Name A.39 RCS TLESS SHARP 2368 LB XF 930 + 4X4 OPT. LB BLACK

Measurem.

Code FTS1900633
 Name A.39 RCS TLESS SHARP 2368 LB XF 930 + 4X4 OPT. LB BLACK

Luminaire Flux	3118.35 lm	Luminaire Power	44.00 W	Efficacy	70.87 lm/W	Efficiency	100.00%
Sources Flux	3118.35 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area	0.021904 m2			Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°	0.005299 m2		
Coordinate system	CG			Symmetry Type	Rotosymmetrical		
Date	17-07-2017			Maximum Gamma Angle	180		
Measurement Distance	0.00			Measurement Flux	3118.35 lm		
LED Flux=4352,8lm LED Power=44W Eff=72% EfcLed=99lm/W EfcLum=71lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		



Luminaire

Code BH26401+BH16204
Name A.39 RCS TLESS SHARP 2368 LB XF 930 + 4X4 OPT. LB BLACK

Measurem.


Code FTS1900633
Name A.39 RCS TLESS SHARP 2368 LB XF 930 + 4X4 OPT. LB BLACK

Luminaire Flux	3118.35 lm	Luminaire Power	44.00 W	Efficacy	70.87 lm/W	Efficiency	100.00%
Sources Flux	3118.35 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3118.35 lm	
LED Flux=4352,8lm LED Power=44W Eff=72% EfcLed=99lm/W EfcLum=71lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.44	OC	0.49	0.98	1.47	1.96	2.44
OB	0.49	0.98	1.47	1.96	2.44	OD	0.49	0.98	1.47	1.96	2.44

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4462.25	4430.18	4045.05	2690.63	476.41	69.49	5.41	0.00	0.00	0.00
OB	4462.25	4430.18	4045.05	2690.63	476.41	69.49	5.41	0.00	0.00	0.00
OC	4462.25	4430.18	4045.05	2690.63	476.41	69.49	5.41	0.00	0.00	0.00
OD	4462.25	4430.18	4045.05	2690.63	476.41	69.49	5.41	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0
1.00	0.98	4462	2693		
2.00	1.96	1116	673		
3.00	2.93	496	299		
4.00	3.91	279	168		
5.00	4.89	178	108		