

Luminaire


Code AT14505
Name A.39 SOS/PLF CTRL EMIS 1480MM 830 ND SIL

Measurement

Code FTS1801850
Name A.39 SOS/PLF CTRL EMIS 1480MM 830 ND SIL

| | | | | | | | |
|---|------------------|-----------------|---------------|-----------------------------|--------------------|------------|--------------------|
| Luminaire Flux | 2373.99 lm | Luminaire Power | 42.00 W | Efficacy | 56.52 lm/W | Efficiency | 100.00% |
| Sources Flux | 2373.99 lm | Maximum value | 596.97 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1482 mm | Width | 45 mm | Height | 85 mm |
| Rectangular Luminous Area | | Length | 1474 mm | Width | 40 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.058960 m2 | | Emitting area on Plane 180° | 0.000000 m2 | | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | 0.000000 m2 | | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | 0.014264 m2 | | |
| Coordinate system | | CG | | Symmetry Type | Double Symmetrical | | |
| Date | | 04-09-2018 | | Maximum Gamma Angle | 180 | | |
| Measurement Distance | | 0.00 | | Measurement Flux | 2373.99 lm | | |
| LED Flux=5788,8lm LED Power=36,25W Eff=41% EfcLed=160lm/W EfcLum=57lm/W CCT=3000K Ra=80 SDCM=2 L70(6K)=50000h | | | | | | | |
| C.I.E. | 72 97 99 100 100 | | | D DIN 5040 | A60 | | |
| F UTE | 1.00 B | | | B NBN | BZ 2 | | |

1482mm x 45mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %

