


Luminaire

Code BH12404+BH16004
 Name A.39 SHARP D+IND 1184 LB 34 300K ND NRO + COVER 2X4 OPT. LB BLACK

Measurem.

Code FTS1900043
 Name A.39 SHARP D+IND 1184 LB 34 300K ND NRO + COVER 2X4 OPT. LB BLACK

Luminaire Flux	4479.59 lm	Luminaire Power	53.00 W	Efficacy	84.52 lm/W	Efficiency	100.00%
Sources Flux	4479.59 lm	Maximum value	894.75 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.002650 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		29-05-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4479.59 lm	
LED Flux=5649,68lm LED Power=44W Eff=79% EfcLed=128lm/W EfcLum=85lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99 100 100 34 100			D DIN 5040		D62	
F UTE	--			B NBN		BZ 1	



Luminaire

Code BH12404+BH16004
Name A.39 SHARP D+IND 1184 LB 34 300K ND NRO + COVER 2X4 OPT. LB BLACK

Measurerm.


Code FTS1900043
Name A.39 SHARP D+IND 1184 LB 34 300K ND NRO + COVER 2X4 OPT. LB BLACK

Luminaire Flux	4479.59 lm	Luminaire Power	53.00 W	Efficacy	84.52 lm/W	Efficiency	100.00%
Sources Flux	4479.59 lm	Maximum value	894.75 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area	0.010952 m2			Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°			0.002650 m2
Coordinate system	CG			Symmetry Type			Double Symmetrical
Date	29-05-2018			Maximum Gamma Angle			180
Measurement Distance	0.00			Measurement Flux			4479.59 lm
LED Flux=5649,68lm LED Power=44W Eff=79% EfcLed=128lm/W EfcLum=85lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99 100 100 34 100			D DIN 5040		D62	
F UTE	--			B NBN		BZ 1	

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.33	0.65	0.98	1.30	1.63	OC	0.33	0.65	0.98	1.30	1.63
OB	0.33	0.65	0.98	1.30	1.63	OD	0.33	0.65	0.98	1.30	1.63

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4008.13	3723.36	2448.35	872.83	148.39	29.89	3.51	0.49	0.00	0.00
OB	4008.13	3723.36	2448.35	872.83	148.39	29.89	3.51	0.49	0.00	0.00
OC	4008.13	3723.36	2448.35	872.83	148.39	29.89	3.51	0.49	0.00	0.00
OD	4008.13	3723.36	2448.35	872.83	148.39	29.89	3.51	0.49	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=18.0°+18.0°	G=0.0
1.00	0.65	4008	2331		
2.00	1.30	1002	583		
3.00	1.95	445	259		
4.00	2.60	251	146		
5.00	3.25	160	93		

H[m]	D[m]	Max lux	Med lux	Beta=18.0°+18.0°	G=0.0
1.00	0.65	4008	2331		
2.00	1.30	1002	583		
3.00	1.95	445	259		
4.00	2.60	251	146		
5.00	3.25	160	93		