

Luminaire

Code BH12405+BH16004
 Name A.39 SHARP D+IND 1184 LB 34 300K ND SIL + COVER 2X4 OPT. LB BLACK

Measurem.

Code FTS1900043
 Name A.39 SHARP D+IND 1184 LB 34 300K ND SIL + COVER 2X4 OPT. LB BLACK

Luminaire Flux	4479.59 lm	Luminaire Power	53.00 W	Efficacy	84.52 lm/W	Efficiency	100.00%
Sources Flux	4479.59 lm	Maximum value	894.75 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002650 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		29-05-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4479.59 lm	
LED Flux=5649,68lm LED Power=44W Eff=79% EfcLed=128lm/W EfcLum=85lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99 100 100 34 100			D DIN 5040		D62	
F UTE	--			B NBN		BZ 1	

1184mm x 40mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 65.99 %
 DLOR 34.01 %
 RN 65.99 %



