

Luminaire

Code 2121C10AHE
Name AOL SYSTEM S 60° SLV TER SX 3500K HE

Measurement

Code FTS2400069
Name AOL SYSTEM S 60° SLV TER SX 3500K HE

Luminaire Flux	815 lm	Luminaire Power	8.0 W	Efficacy	101.875 lm/W	Efficiency	100.00%
Source Flux	815 lm	Maximum value	162.58 cd/klm	Position	C=20.00 G=5.00	CG	Sym. on planes 0-180
Rectangular Luminaire		Length	475 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	475 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.023750 m ²		Emitting area on Plane 180°		0.023750 m ²	
Emitting area on Plane 0°		0.023750 m ²		Emitting area on Plane 270°		0.002500 m ²	
Emitting area on Plane 90°		0.002500 m ²		Glare area at 76°		0.028790 m ²	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		26-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		815 lm	
LED Flux=1066lm LED Power=8W Eff=76% EfcLed=133lm/W EfcLum=102lm/W CCT=3500K Ra=90 R9=50 SDCM=3 L70(10k)=60000h							
C.I.E.	33 61 83 70 100			D DIN 5040	B21		
F UTE	0.70 H + 0.30 T			B NBN	BZ 6		

