

## Luminaire

Code 1045110A  
Name CASTORE 14 S

## Measurerm.

Code FTS1801501  
Name CASTORE 14 S

Luminaire Flux	402 lm	Luminaire Power	5.0 W	Efficacy	80.464 lm/W	Efficiency	85.60%
Source Flux	470 lm	Maximum value	86.18 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	140 mm	Height	140 mm		
Round Luminous Area		Diam.	140 mm	Height	70 mm		
Horizontal Luminous Area		0.015394 m <sup>2</sup>		Emitting area on Plane 180°		0.019600 m <sup>2</sup>	
Emitting area on Plane 0°		0.019600 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.022742 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		16-12-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		470 lm	


Lamping=LED DIM 1x5W (E14) CCT=2700K CRI=80

C.I.E. 27 52 77 59 86  
F UTE 0.50 J + 0.35 T

D DIN 5040  
B NBN

C11  
BZ 8 / 0.8 / BZ 7 / 1.25 / BZ 8 / 2.5 / BZ 7

Diam=140mm



Semipiani C

180.0 ——— 0.0

ULOR 35.36 %

DLOR 50.24 %

RN 41.30 %

