

Luminaire

Code M0569W83+M109800+M282007

Name CATA TIR BINARIO STABLE WHITE UNITA' OTTICA 3000K DIMM DALI-SWITCHDIM + OTTICA WIDE FLOOD +LENTE ELLITTICA

Measurement

Code FTS1503362

Name CATA TIR BINARIO STABLE WHITE UNITA' OTTICA 3000K DIMM DALI-SWITCHDIM + OTTICA WIDE FLOOD +LENTE ELLITTICA

Luminaire Flux	1174.66 lm	Luminaire Power	22.00 W	Efficacy	53.39 lm/W	Efficiency	100.00%
Lamps Flux	1174.66 lm	Maximum value	1078.06 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Round Luminaire Round Luminous Area	Diam. 130 mm Diam. 75 mm	Height	176 mm	Height	50 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.004418 m2 0.003750 m2 0.003750 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°			0.003750 m2 0.003750 m2 0.004707 m2		
Coordinate system	CG	Symmetry Type			Double Symmetrical		
Date	07-10-2015	Maximum Gamma Angle			90		
Measurement Distance	0.00	Measurement Flux			1174.66 lm		
LED Flux=1811,5lm LED Power=17,5W Eff=65% EfcLed=104lm/W EfcLum=53lm/W Ra=90 SDCM=2 L70(6K)=36000h							
C.I.E.	81 95 99 100 100	D DIN 5040		A60			
F UTE	1.00 B	B NBN		BZ 1			



