

Luminaire

Code M324205
 Name EVERYTHING 150 TONDO TRIMLESS ORIENTABILE LED FLOOD DEFL. METALIZZATO 2700K

Measurem.

Code FTS1602596
 Name EVERYTHING 150 TONDO TRIMLESS ORIENTABILE LED FLOOD DEFL. METALIZZATO 2700K

Luminaire Flux	2327.60 lm	Luminaire Power	24.00 W	Efficacy	96.98 lm/W	Efficiency	100.00%
Sources Flux	2327.60 lm	Maximum value	5207.68 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	150 mm	Height	137 mm		
Round Luminous Area		Diam.	120 mm	Height	0 mm		
Horizontal Luminous Area		0.011310 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002736 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		11-03-2015		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		2327.60 lm	


LED Flux=2645lm LED Power=24W Eff=88% EfcLed=110lm/W EfcLum=97lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E. 99 100 100 100 100
 F UTE --

D DIN 5040
 B NBN

A60
 BZ 1


Diam=150mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR100.00 %
 RN 0.00 %



Luminaire

Code M324205
Name EVERYTHING 150 TONDO TRIMLESS ORIENTABILE LED FLOOD DEFL. METALIZZATO 2700K

Measurement


Code FTS1602596
Name EVERYTHING 150 TONDO TRIMLESS ORIENTABILE LED FLOOD DEFL. METALIZZATO 2700K

Luminaire Flux	2327.60 lm	Luminaire Power	24.00 W	Efficacy	96.98 lm/W	Efficiency	100.00%
Sources Flux	2327.60 lm	Maximum value	5207.68 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	150 mm	Height	137 mm		
Round Luminous Area		Diam.	120 mm	Height	0 mm		
Horizontal Luminous Area		0.011310 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002736 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		11-03-2015		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		2327.60 lm	
LED Flux=2645lm LED Power=24W Eff=88% EfcLed=110lm/W EfcLum=97lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.17	0.33	0.50	0.66	0.83	OC	0.17	0.33	0.50	0.66	0.83
OB	0.17	0.33	0.50	0.66	0.83	OD	0.17	0.33	0.50	0.66	0.83

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	12121.39	9776.78	2629.03	968.35	424.26	32.36	5.89	0.00	0.00	0.00
OB	12121.39	9776.78	2629.03	968.35	424.26	32.36	5.89	0.00	0.00	0.00
OC	12121.39	9776.78	2629.03	968.35	424.26	32.36	5.89	0.00	0.00	0.00
OD	12121.39	9776.78	2629.03	968.35	424.26	32.36	5.89	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=9.4°+9.4°	G=0.0
1.00	0.33	12121	7632		
2.00	0.66	3030	1908		
3.00	0.99	1347	848		
4.00	1.32	758	477		
5.00	1.65	485	305		