

Luminaire


Code 1859010A
Name DREISPITZ 120 S VERT DIF GRN

Measurement

Code FTS2500036
Name DREISPITZ 120 S VERT DIF GRN

| | | | | | | | |
|---|-----------------|-------------------------|---------------|-----------------------------|----------------|-------------------------|--------------------|
| Luminaire Flux | 4510 lm | Luminaire Power | 40.0 W | Efficacy | 112.750 lm/W | Efficiency | 100.00% |
| Source Flux | 4510 lm | Maximum value | 113.37 cd/klm | Position | C=0.00 G=58.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1132 mm | Width | 99 mm | Height | 104 mm |
| Rectangular Luminous Area | | Length | 1120 mm | Width | 90 mm | Height | 60 mm |
| Horizontal Luminous Area | | 0.100800 m ² | | Emitting area on Plane 180° | | 0.067200 m ² | |
| Emitting area on Plane 0° | | 0.067200 m ² | | Emitting area on Plane 270° | | 0.005400 m ² | |
| Emitting area on Plane 90° | | 0.005400 m ² | | Glare area at 76° | | 0.089590 m ² | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 13-02-2025 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 4510 lm | |
| LED Flux=6090lm LED Power=36W Eff=74% EfcLed=171lm/W EfcLum=113lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h | | | | | | | |
| C.I.E. | 28 55 79 51 100 | | | D DIN 5040 | | C11 | |
| F UTE | 0.51 J + 0.49 T | | | B NBN | | BZ 7 | |

1132mm x 99mm



Semipiani C

180.0 ——— 0.0
270.0 ——— 90.0

ULOR 48.87 %

DLOR 51.13 %

RN 48.87 %

