

## Luminaire


Code 1862000A  
Name DREISPITZ 120 C/W DIF SIL

## Measurum.

Code FTS2500038  
Name DREISPITZ 120 C/W DIF SIL

Luminaire Flux	3287 lm	Luminaire Power	28.0 W	Efficacy	117.393 lm/W	Efficiency	100.00%
Source Flux	3287 lm	Maximum value	181.50 cd/klm	Position	C=35.00 G=2.00	CG	Double Symmetrical
Rectangular Luminaire	Length	1132 mm	Width	99 mm	Height	74 mm	
Rectangular Luminous Area	Length	1120 mm	Width	60 mm	Height	29 mm	
Horizontal Luminous Area	0.067200 m2		Emitting area on Plane 180°	0.033600 m2			
Emitting area on Plane 0°	0.033600 m2		Emitting area on Plane 270°	0.001800 m2			
Emitting area on Plane 90°	0.001800 m2		Glare area at 76°	0.048859 m2			
Coordinate system	CG		Symmetry Type	Double Symmetrical			
Date	13-02-2025		Maximum Gamma Angle	180			
Measurement Distance	0.00		Measurement Flux	3287 lm			
LED Flux=4060lm LED Power=24W Eff=81% EfcLed=171lm/W EfcLum=117lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h							
C.I.E.	37 65 85 69 100	D DIN 5040	B21				
F UTE	0.69 H + 0.31 T	B NBN	BZ 6				

1132mm x 99mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 30.72 %  
DLOR 69.28 %  
RN 30.72 %

