
Luminaire
Code 2140C10AHEB
Name AOL SYSTEM C/W LIN180 SLV TER 3500K HEB
Measurem.
Code FTS2600173
Name AOL SYSTEM C/W LIN180 SLV TER 3500K HEB

Luminaire Flux	3400 lm	Luminaire Power	33.0 W	Efficacy	103.030 lm/W	Efficiency	100.00%
Source Flux	3400 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical


Rectangular Luminaire	Length	1800 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area	Length	1800 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area	0.090000 m2		Emitting area on Plane 180°		0.090000 m2	
Emitting area on Plane 0°	0.090000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°	0.002500 m2		Glare area at 76°		0.109100 m2	
Coordinate system	CG		Symmetry Type		Double Symmetrical	
Date	26-03-2024		Maximum Gamma Angle		180	
Measurement Distance	0.00		Measurement Flux		3400 lm	

LED Flux=4262lm LED Power=33W Eff=80% EfcLed=129lm/W EfcLum=103lm/W CCT=3500K Ra=90 R9=50 SDCM=3 L70(10k)=60000h


C.I.E.	33 60 82 69 100	D DIN 5040	B21
F UTE	0.69 H + 0.31 T	B NBN	BZ 6



1800mm x 50mm



Semipiani C



ULOR 31.35 %
DLOR 68.65 %
RN 31.35 %