Luminaire
Code 2159010AHEB
Name AOL SYSTEM C MODULO X 3000K HEB
Measurem.
Code FTS2600169
Name AOL SYSTEM C MODULO X 3000K HEB


Luminaire Flux	253 lm	Luminaire Power	3.0 W	Efficacy	84.333 lm/W	Efficiency	100.00%
Source Flux	253 lm	Maximum value	275.28 cd/klm	Position	C=5.00 G=3.00	CG	Double Symmetrical

Rectangular Luminaire	Length	87 mm	Width	87 mm	Height	50 mm
Rectangular Luminous Area	Length	87 mm	Width	87 mm	Height	50 mm
Horizontal Luminous Area	0.007569 m2		Emitting area on Plane 180°		0.004350 m2	
Emitting area on Plane 0°	0.004350 m2		Emitting area on Plane 270°		0.004350 m2	
Emitting area on Plane 90°	0.004350 m2		Glare area at 76°		0.006052 m2	
Coordinate system	CG		Symmetry Type		Double Symmetrical	
Date	26-03-2024		Maximum Gamma Angle		180	
Measurement Distance	0.00		Measurement Flux		253 lm	

LED Flux=355lm LED Power=3W Eff=71% EfcLed=118lm/W EfcLum=84lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h


C.I.E.	43 72 90 84 100	D DIN 5040	B31
F UTE	0.84 G + 0.16 T	B NBN	BZ 5

87mm x 87mm



Semipiani C

180.0 — 0.0
270.0 — 90.0



ULOR 16.20 %
DLOR 83.80 %
RN 16.20 %

Luminaire
Code 2159010AHEB
Name AOL SYSTEM C MODULO X 3000K HEB
Measurem.
Code FTS2600169
Name AOL SYSTEM C MODULO X 3000K HEB

Luminaire Flux	253 lm	Luminaire Power	3.0 W	Efficacy	84.333 lm/W	Efficiency	100.00%
Source Flux	253 lm	Maximum value	275.28 cd/klm	Position	C=5.00 G=3.00	CG	Double Symmetrical

Rectangular Luminaire	Length 87 mm		Width 87 mm		Height 50 mm
Rectangular Luminous Area	Length 87 mm		Width 87 mm		Height 50 mm
Horizontal Luminous Area	0.007569 m2		Emitting area on Plane 180°		0.004350 m2
Emitting area on Plane 0°	0.004350 m2		Emitting area on Plane 270°		0.004350 m2
Emitting area on Plane 90°	0.004350 m2		Glare area at 76°		0.006052 m2
Coordinate system	CG		Symmetry Type		Double Symmetrical
Date	26-03-2024		Maximum Gamma Angle		180
Measurement Distance	0.00		Measurement Flux		253 lm

LED Flux=355lm LED Power=3W Eff=71% EfcLed=118lm/W EfcLum=84lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h


C.I.E.	43 72 90 84 100	D DIN 5040	B31
F UTE	0.84 G + 0.16 T	B NBN	BZ 5

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.50	3.00	4.49	5.99	7.49	OC	1.46	2.92	4.38	5.85	7.31
OB	1.50	3.00	4.49	5.99	7.49	OD	1.46	2.92	4.38	5.85	7.31

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	69.46	69.04	66.04	60.45	52.93	44.67	35.81	27.75	19.74	13.16
OB	69.46	69.04	66.04	60.45	52.93	44.67	35.81	27.75	19.74	13.16
OC	69.46	69.08	65.89	60.03	52.35	43.84	35.23	27.30	19.32	12.78
OD	69.46	69.08	65.89	60.03	52.35	43.84	35.23	27.30	19.32	12.78



H[m]	D[m]	Max lux	Med lux	Alpha=56.3°+56.3° G=0.0
1.00	3.00	69	17	
2.00	5.99	17	4	
3.00	8.99	8	2	
4.00	11.98	4	1	
5.00	14.98	3	1	

H[m]	D[m]	Max lux	Med lux	Beta=55.6°+55.6° G=0.0
1.00	2.92	69	17	
2.00	5.85	17	4	
3.00	8.77	8	2	
4.00	11.69	4	1	
5.00	14.61	3	1	