

Luminaire

Code FU52204+AP91400
Name VECTOR 55 PENDANT FUNIVIA 940 WF NRO

Measurem.

Code FTS1800392-B
Name VECTOR 55 PENDANT FUNIVIA 940 WF NRO

Luminaire Flux	1471 lm	Luminaire Power	19.0 W	Efficacy	77.421 lm/W	Efficiency	100.00%
Source Flux	1471 lm	Maximum value	4326.59 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	130 mm		
Round Luminous Area		Diam.	48 mm	Height	0 mm		
Horizontal Luminous Area		0.001810 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000438 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		26-01-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1471 lm	
LED Flux=2694lm LED Power=17W Eff=55% EfcLed=155lm/W EfcLum=77lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(9k)>=50000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Diam=55mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code FU52204+AP91400
Name VECTOR 55 PENDANT FUNIVIA 940 WF NRO

Measurem.


Code FTS1800392-B
Name VECTOR 55 PENDANT FUNIVIA 940 WF NRO

Luminaire Flux	1471 lm	Luminaire Power	19.0 W	Efficacy	77.421 lm/W	Efficiency	100.00%
Source Flux	1471 lm	Maximum value	4326.59 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	130 mm		
Round Luminous Area		Diam.	48 mm	Height	0 mm		
Horizontal Luminous Area		0.001810 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000438 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		26-01-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1471 lm	
LED Flux=2694lm LED Power=17W Eff=55% EfcLed=155lm/W EfcLum=77lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(9k)>=50000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.25	0.50	0.76	1.01	1.26	OC	0.25	0.50	0.76	1.01	1.26
OB	0.25	0.50	0.76	1.01	1.26	OD	0.25	0.50	0.76	1.01	1.26

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	6364.41	5839.59	2876.68	228.80	20.90	5.17	1.76	0.57	0.39	0.33
OB	6364.41	5839.59	2876.68	228.80	20.90	5.17	1.76	0.57	0.39	0.33
OC	6364.41	5839.59	2876.68	228.80	20.90	5.17	1.76	0.57	0.39	0.33
OD	6364.41	5839.59	2876.68	228.80	20.90	5.17	1.76	0.57	0.39	0.33



H[m]	D[m]	Max lux	Med lux	Alpha=14.1°+14.1°	G=0.0
1.00	0.50	6364	3949		
2.00	1.01	1591	987		
3.00	1.51	707	439		
4.00	2.01	398	247		
5.00	2.52	255	158		