

Luminaire

Code A240610
Name NUR SOSPENSIONE HALO ANODIZZATO

Measurement

Code FTS0002568
Name NUR SOSPENSIONE HALO ANODIZZATO

Luminaire Flux	2427 lm	Luminaire Power	205.0 W	Efficacy	11.837 lm/W	Efficiency	57.78%
Source Flux	4200 lm	Maximum value	249.20 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	550 mm 300 mm	Width Height	550 mm 0 mm	Height	430 mm
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.070686 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.017100 m2	
Coordinate system Date Measurement Distance		CG 09-02-2004 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 4200 lm	
64404							
C.I.E. F UTE	63 90 98 94 58 0.55 C + 0.03 T			D DIN 5040 B NBN	A51 BZ 3		


550mm x 550mm



Semipiani C

180.0 ——— 0.0

ULOR 3.23 %
DLOR 54.55 %
RN 5.59 %



Luminaire

Code A240610
Name NUR SOSPENSIONE HALO ANODIZZATO

Measurment.


Code FTS0002568
Name NUR SOSPENSIONE HALO ANODIZZATO

Luminaire Flux	2427 lm	Luminaire Power	205.0 W	Efficacy	11.837 lm/W	Efficiency	57.78%
Source Flux	4200 lm	Maximum value	249.20 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	550 mm 300 mm	Width Height	550 mm 0 mm	Height	430 mm
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.070686 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.017100 m2	
Coordinate system Date Measurement Distance		CG 09-02-2004 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 4200 lm	
64404							
C.I.E. F UTE	63 90 98 94 58 0.55 C + 0.03 T			D DIN 5040 B NBN	A51 BZ 3		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.01	2.02	3.03	4.04	5.05	OC	1.01	2.02	3.03	4.04	5.05
OB	1.01	2.02	3.03	4.04	5.05	OD	1.01	2.02	3.03	4.04	5.05

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1046.64	1046.36	1022.97	961.18	885.88	537.61	278.49	135.42	56.73	14.96
OB	1046.64	1046.36	1022.97	961.18	885.88	537.61	278.49	135.42	56.73	14.96
OC	1046.64	1046.36	1022.97	961.18	885.88	537.61	278.49	135.42	56.73	14.96
OD	1046.64	1046.36	1022.97	961.18	885.88	537.61	278.49	135.42	56.73	14.96



H[m]	D[m]	Max lux	Med lux	Alpha=45.3°+45.3°	G=0.0
1.00	2.02	1047	425		
2.00	4.04	262	106		
3.00	6.06	116	47		
4.00	8.09	65	27		
5.00	10.11	42	17		