

Luminaire


Code 2063010A
Name RIPPLE S CLUSTER (3)

Measurem.

Code FTS2001263
Name RIPPLE S CLUSTER (3)

Luminaire Flux	5510.14 lm	Luminaire Power	89.00 W	Efficacy	61.91 lm/W	Efficiency	100.00%
Lamps Flux	5510.14 lm	Maximum value	353.72 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	1530 mm	Width	1350 mm	Height	30 mm
Rectangular Luminous Area		Length	1500 mm	Width	1320 mm	Height	0 mm
Horizontal Luminous Area	1.980000 m2			Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°	0.479005 m2		
Coordinate system	CG			Symmetry Type	Rotosymmetrical		
Date	12-11-2020			Maximum Gamma Angle	180		
Measurement Distance	0.00			Measurement Flux	5510.14 lm		
LED Flux=11410,53lm LED Power=84W Eff=48% EfcLed=136lm/W EfcLum=62lm/W CCT=3000 Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	47 79 96 100 100			D DIN 5040	A30		
F UTE	1.00 E			B NBN	BZ 5 / 0.8 / BZ 4		

1530mm x 1350mm




Semipiani C

180.0 ——— 0.0

ULOR 0.01 %

DLOR 99.99 %

RN 0.01 %



Luminaire

Code 2063010A
Name RIPPLE S CLUSTER (3)

Measur.

Code FTS2001263
Name RIPPLE S CLUSTER (3)

Luminaire Flux	5510.14 lm	Luminaire Power	89.00 W	Efficacy	61.91 lm/W	Efficiency	100.00%
Lamps Flux	5510.14 lm	Maximum value	353.72 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	1530 mm	Width	1350 mm	Height	30 mm
Rectangular Luminous Area		Length	1500 mm	Width	1320 mm	Height	0 mm
Horizontal Luminous Area	1.980000 m2	Emitting area on Plane 180°		Emitting area on Plane 270°		Emitting area on Plane 90°	0.479005 m2
Emitting area on Plane 0°	0.000000 m2						
Emitting area on Plane 90°	0.000000 m2						
Coordinate system	CG	Symmetry Type		Maximum Gamma Angle		Measurement Flux	5510.14 lm
Date	12-11-2020						
Measurement Distance	0.00						


LED Flux=11410,53lm LED Power=84W Eff=48% EfcLed=136lm/W EfcLum=62lm/W CCT=3000 Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	47 79 96 100 100	D DIN 5040	A30
F UTE	1.00 E	B NBN	BZ 5 / 0.8 / BZ 4

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.48	2.95	4.43	5.91	7.38	OC	1.48	2.95	4.43	5.91	7.38
OB	1.48	2.95	4.43	5.91	7.38	OD	1.48	2.95	4.43	5.91	7.38

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1949.02	1938.20	1864.05	1725.67	1529.62	1285.63	1001.61	687.45	360.16	82.71
OB	1949.02	1938.20	1864.05	1725.67	1529.62	1285.63	1001.61	687.45	360.16	82.71
OC	1949.02	1938.20	1864.05	1725.67	1529.62	1285.63	1001.61	687.45	360.16	82.71
OD	1949.02	1938.20	1864.05	1725.67	1529.62	1285.63	1001.61	687.45	360.16	82.71



H[m]	D[m]	Max lux	Med lux	Alpha=55.9°+55.9°	G=0.0
1.00	2.95	1949	478		
2.00	5.91	487	120		
3.00	8.86	217	53		
4.00	11.81	122	30		
5.00	14.77	78	19		