


## Luminaire

Code AF24901+AF95204  
 Name SHARP RECESSED TRIM 16X 48W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

## Measurem.

Code FTS1902039  
 Name SHARP RECESSED TRIM 16X 48W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Luminaire Flux	2854.72 lm	Luminaire Power	44.00 W	Efficacy	64.88 lm/W	Efficiency	100.00%
Lamps Flux	2854.72 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	612 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2854.72 lm	
LED Flux=3984.8lm LED Power=44W Eff=72% EfcLed=91lm/W EfcLum=65lm/W CCT=2700K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



## Luminaire

Code AF24901+AF95204  
 Name SHARP RECESSED TRIM 16X 48W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

## Measur.


Code FTS1902039  
 Name SHARP RECESSED TRIM 16X 48W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Luminaire Flux	2854.72 lm	Luminaire Power	44.00 W	Efficacy	64.88 lm/W	Efficiency	100.00%
Lamps Flux	2854.72 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	612 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2854.72 lm	
LED Flux=3984.8lm LED Power=44W Eff=72% EfcLed=91lm/W EfcLum=65lm/W CCT=2700K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100		D DIN 5040	A60
F UTE	--					B NBN	BZ 1

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.44	OC	0.49	0.98	1.47	1.96	2.44
OB	0.49	0.98	1.47	1.96	2.44	OD	0.49	0.98	1.47	1.96	2.44

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4085.01	4055.64	3703.08	2463.16	436.13	63.62	4.96	0.00	0.00	0.00
OB	4085.01	4055.64	3703.08	2463.16	436.13	63.62	4.96	0.00	0.00	0.00
OC	4085.01	4055.64	3703.08	2463.16	436.13	63.62	4.96	0.00	0.00	0.00
OD	4085.01	4055.64	3703.08	2463.16	436.13	63.62	4.96	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0
1.00	0.98	4085	2465		
2.00	1.96	1021	616		
3.00	2.93	454	274		
4.00	3.91	255	154		
5.00	4.89	163	99		