

Luminaire

Code AP10204+AP91200
 Name VECTOR 55 MAGNET 930 FL DALI NRO + LENS FOR ELLIPTICAL EMISSION

Measurem.

Code FTS1800327
 Name VECTOR 55 MAGNET 930 FL DALI NRO + LENS FOR ELLIPTICAL EMISSION

| | | | | | | | |
|--|-------------------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 926.90 lm | Luminaire Power | 26.00 W | Efficacy | 35.65 lm/W | Efficiency | 100.00% |
| Lamps Flux | 926.90 lm | Maximum value | 3209.14 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Round Luminaire | | Diam. | 55 mm | Height | 130 mm | | |
| Round Luminous Area | | Diam. | 47 mm | Height | 0 mm | | |
| Horizontal Luminous Area | | 0.001735 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.000420 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 04-05-2018 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 926.90 lm | |
| LED Flux=2346lm LED Power=21W Eff=40% EfcLed=112lm/W EfcLum=36lm/W CCT=3000K Ra=90 SDCM=3 L70(6K)=50000h | | | | | | | |
| C.I.E. | 95 98 100 100 100 | | | D DIN 5040 | A60 | | |
| F UTE | 1.00 A | | | B NBN | BZ 1 | | |



