

Luminaire

Code AP10101+AP91200
 Name VECTOR 55 MAGNET 930 SP DALI BCO + LENS FOR ELLIPTICAL EMISSION

Measurem.

Code FTS1800323
 Name VECTOR 55 MAGNET 930 SP DALI BCO + LENS FOR ELLIPTICAL EMISSION

| | | | | | | | |
|--|-------------------|------------------|----------------|-----------------------------|---------------|------------|--------------------|
| Luminaire Flux | 983.91 lm | Luminaire Power | 26.00 W | Efficacy | 37.84 lm/W | Efficiency | 100.00% |
| Lamps Flux | 983.91 lm | Maximum value | 3842.70 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Round Luminaire | | Diam. | 55 mm | Height | 130 mm | | |
| Round Luminous Area | | Diam. | 47 mm | Height | 0 mm | | |
| Horizontal Luminous Area | 0.001735 m2 | | | Emitting area on Plane 180° | 0.000000 m2 | | |
| Emitting area on Plane 0° | 0.000000 m2 | | | Emitting area on Plane 270° | 0.000000 m2 | | |
| Emitting area on Plane 90° | 0.000000 m2 | | | Glare area at 76° | 0.000420 m2 | | |
| Coordinate system | CG | Symmetry Type | | Maximum Gamma Angle | 180 | | Double Symmetrical |
| Date | 03-05-2018 | Measurement Flux | | | 180 | | |
| Measurement Distance | 0.00 | | | | 983.91 lm | | |
| LED Flux=2346lm LED Power=21W Eff=42% EfcLed=112lm/W EfcLum=38lm/W CCT=3000K Ra=90 SDCM=3 L70(6K)=50000h | | | | | | | |
| C.I.E. | 95 98 100 100 100 | D DIN 5040 | | A60 | | | |
| F UTE | 1.00 A | B NBN | | BZ 1 | | | |



