


Luminaire

Code AN00704+AP90400
Name VECTOR 40 TRACK 930 FL DALI NRO + ANTI-DAZZLE LOUVRE

Measurement

Code FTS1800633
Name VECTOR 40 TRACK 930 FL DALI NRO + ANTI-DAZZLE LOUVRE

Luminaire Flux	300.39 lm	Luminaire Power	10.00 W	Efficacy	30.04 lm/W	Efficiency	100.00%
Lamps Flux	300.39 lm	Maximum value	6075.95 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area	Diam. 40 mm Diam. 27 mm	Height	103 mm	Height	0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.000573 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.000000 m2 0.000000 m2 0.000139 m2				
Coordinate system	CG	Symmetry Type	Rotosymmetrical				
Date	14-05-2018	Maximum Gamma Angle	180				
Measurement Distance	0.00	Measurement Flux	300.39 lm				
LED Flux=846,4lm LED Power=8W Eff=35% EfcLed=106lm/W EfcLum=30lm/W CCT=3000K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	99 100 100 100 100	D DIN 5040	A60				
F UTE	--	B NBN	BZ 1				



Luminaire

Code AN00704+AP90400
Name VECTOR 40 TRACK 930 FL DALI NRO + ANTI-DAZZLE LOUVRE

Measurement

Code FTS1800633
Name VECTOR 40 TRACK 930 FL DALI NRO + ANTI-DAZZLE LOUVRE

Luminaire Flux	300.39 lm	Luminaire Power	10.00 W	Efficacy	30.04 lm/W	Efficiency	100.00%
Lamps Flux	300.39 lm	Maximum value	6075.95 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	103 mm		
Round Luminous Area		Diam.	27 mm	Height	0 mm		
Horizontal Luminous Area	0.000573 m2			Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°		0.000139 m2	
Coordinate system	CG	Symmetry Type		Maximum Gamma Angle		Rotosymmetrical	
Date	14-05-2018	Measurement Flux				180	
Measurement Distance	0.00					300.39 lm	


LED Flux=846,4lm LED Power=8W Eff=35% EfcLed=106lm/W EfcLum=30lm/W CCT=3000K Ra=90 SDCM=2 L70(6K)=50000h

C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.36	0.54	0.72	0.90	OC	0.18	0.36	0.54	0.72	0.90
OB	0.18	0.36	0.54	0.72	0.90	OD	0.18	0.36	0.54	0.72	0.90

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1825.16	1527.85	433.61	81.76	10.41	2.44	0.68	0.26	0.22	0.18
OB	1825.16	1527.85	433.61	81.76	10.41	2.44	0.68	0.26	0.22	0.18
OC	1825.16	1527.85	433.61	81.76	10.41	2.44	0.68	0.26	0.22	0.18
OD	1825.16	1527.85	433.61	81.76	10.41	2.44	0.68	0.26	0.22	0.18



H[m]	D[m]	Max lux	Med lux	Alpha=10.2°+10.2°	G=0.0
1.00	0.36	1825	1149		
2.00	0.72	456	287		
3.00	1.08	203	128		
4.00	1.43	114	72		
5.00	1.79	73	46		