


## Luminaire

Code AN10118+AP91400  
 Name VECTOR 55 TRACK 930 SP ND BR.COPPER + ANTI-DAZZLE LOUVRE

## Measurem.

Code FTS2001128  
 Name VECTOR 55 TRACK 930 SP ND BR.COPPER + ANTI-DAZZLE LOUVRE

Luminaire Flux	985.55 lm	Luminaire Power	25.00 W	Efficacy	39.42 lm/W	Efficiency	100.00%
Lamps Flux	985.55 lm	Maximum value	8558.76 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	55 mm 47 mm	Height Height	130 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.001735 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000420 m2	
Coordinate system Date Measurement Distance		CG 09-05-2018 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 985.55 lm	
LED Flux=2346lm LED Power=21W Eff=42% EfcLed=112lm/W EfcLum=39lm/W CCT=3000K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E. F UTE	100 100 100 100 100 --			D DIN 5040 B NBN	A60 BZ 1		



## Luminaire

Code AN10118+AP91400  
Name VECTOR 55 TRACK 930 SP ND BR.COPPER + ANTI-DAZZLE LOUVRE

## Measurement


Code FTS2001128  
Name VECTOR 55 TRACK 930 SP ND BR.COPPER + ANTI-DAZZLE LOUVRE

Luminaire Flux	985.55 lm	Luminaire Power	25.00 W	Efficacy	39.42 lm/W	Efficiency	100.00%
Lamps Flux	985.55 lm	Maximum value	8558.76 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam.	55 mm 47 mm	Height	130 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.001735 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000420 m2	
Coordinate system Date Measurement Distance		CG 09-05-2018 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 985.55 lm	
LED Flux=2346lm LED Power=21W Eff=42% EfcLed=112lm/W EfcLum=39lm/W CCT=3000K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E. F UTE	100 100 100 100 100 --			D DIN 5040 B NBN	A60 BZ 1		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.14	0.29	0.43	0.58	0.72	OC	0.14	0.29	0.43	0.58	0.72
OB	0.14	0.29	0.43	0.58	0.72	OD	0.14	0.29	0.43	0.58	0.72

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	8435.09	6725.70	1174.89	164.92	13.92	3.97	1.38	0.47	0.38	0.28
OB	8435.09	6725.70	1174.89	164.92	13.92	3.97	1.38	0.47	0.38	0.28
OC	8435.09	6725.70	1174.89	164.92	13.92	3.97	1.38	0.47	0.38	0.28
OD	8435.09	6725.70	1174.89	164.92	13.92	3.97	1.38	0.47	0.38	0.28



H[m]	D[m]	Max lux	Med lux	Alpha=8.2°+8.2°	G=0.0
1.00	0.29	8435	5470		
2.00	0.58	2109	1368		
3.00	0.87	937	608		
4.00	1.16	527	342		
5.00	1.45	337	219		