


Luminaire

Code AN31818
Name VECTOR 95 TRACK 927 WL DALI EUTRAC BR.COPPER

Measurem.

Code FTS1901163
Name VECTOR 95 TRACK 927 WL DALI EUTRAC BR.COPPER

Luminaire Flux	2559.15 lm	Luminaire Power	30.00 W	Efficacy	85.30 lm/W	Efficiency	100.00%
Lamps Flux	2559.15 lm	Maximum value	1223.92 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	95 mm 75 mm	Height Height	210 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.004418 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.001069 m2	
Coordinate system Date Measurement Distance		CG 27-03-2019 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 2559.15 lm	
LED Flux=3300lm LED Power=27.5W Eff=78% EfcLed=120lm/W EfcLum=85lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E. F UTE	99 --	100 --	100 --	100 --	D DIN 5040 B NBN	A60 BZ 1	



Luminaire

Code AN31818
Name VECTOR 95 TRACK 927 WL DALI EUTRAC BR.COPPER

Measurement


Code FTS1901163
Name VECTOR 95 TRACK 927 WL DALI EUTRAC BR.COPPER

Luminaire Flux	2559.15 lm	Luminaire Power	30.00 W	Efficacy	85.30 lm/W	Efficiency	100.00%
Lamps Flux	2559.15 lm	Maximum value	1223.92 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	95 mm	Height	210 mm		
Round Luminous Area		Diam.	75 mm	Height	0 mm		
Horizontal Luminous Area	0.004418 m2			Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°		0.001069 m2	
Coordinate system	CG			Symmetry Type		Rotosymmetrical	
Date	27-03-2019			Maximum Gamma Angle		180	
Measurement Distance	0.00			Measurement Flux		2559.15 lm	
LED Flux=3300lm LED Power=27.5W Eff=78% EfcLed=120lm/W EfcLum=85lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	99 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.57	1.14	1.70	2.27	2.84	OC	0.57	1.14	1.70	2.27	2.84
OB	0.57	1.14	1.70	2.27	2.84	OD	0.57	1.14	1.70	2.27	2.84

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	3132.20	3074.71	2919.48	2292.91	509.25	27.01	2.86	1.49	0.98	0.49
OB	3132.20	3074.71	2919.48	2292.91	509.25	27.01	2.86	1.49	0.98	0.49
OC	3132.20	3074.71	2919.48	2292.91	509.25	27.01	2.86	1.49	0.98	0.49
OD	3132.20	3074.71	2919.48	2292.91	509.25	27.01	2.86	1.49	0.98	0.49



H[m]	D[m]	Max lux	Med lux	Alpha=29.6°+29.6°	G=0.0
1.00	1.14	3132	1721		
2.00	2.27	783	430		
3.00	3.41	348	191		
4.00	4.54	196	108		
5.00	5.68	125	69		