

Luminaire

Code 1201T00A
Name Alphabet of light - T

Measurem.

Code FTS1700207-A
Name Alphabet of light - T

Luminaire Flux	1674 lm	Luminaire Power	20.0 W	Efficacy	83.706 lm/W	Efficiency	100.00%
Source Flux	1674 lm	Maximum value	114.12 cd/klm	Position	C=90.00 G=89.00	CG	Double Symmetrical
Rectangular Luminaire		Length	50 mm	Width	650 mm	Height	950 mm
Rectangular Luminous Area		Length	50 mm	Width	650 mm	Height	949 mm
Horizontal Luminous Area		0.032500 m2		Emitting area on Plane 180°		0.047500 m2	
Emitting area on Plane 0°		0.047500 m2		Emitting area on Plane 270°		0.617500 m2	
Emitting area on Plane 90°		0.617500 m2		Glare area at 76°		0.053952 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		10-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1674 lm	


LED Flux=1908lm LED Power=20W Eff=88% EfcLed=95lm/W EfcLum=84lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=36000h

C.I.E. 21 46 73 50 100
F UTE 0.50 J + 0.50 T

D DIN 5040
B NBN

C11
BZ 9

50mm x 650mm



Semipiani C

180.0 ——— 0.0
270.0 ——— 90.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %

