

## Luminaire


Code 1202e00A  
Name Alphabet of light - e

## Measurerm.

Code FTS1700166-A  
Name Alphabet of light - e

Luminaire Flux	1971 lm	Luminaire Power	22.0 W	Efficacy	89.597 lm/W	Efficiency	100.00%
Source Flux	1971 lm	Maximum value	114.12 cd/klm	Position	C=90.00 G=89.00	CG	Double Symmetrical
Rectangular Luminaire		Length	50 mm	Width	650 mm	Height	650 mm
Rectangular Luminous Area		Length	50 mm	Width	650 mm	Height	649 mm
Horizontal Luminous Area		0.032500 m <sup>2</sup>		Emitting area on Plane 180°		0.032500 m <sup>2</sup>	
Emitting area on Plane 0°		0.032500 m <sup>2</sup>		Emitting area on Plane 270°		0.422500 m <sup>2</sup>	
Emitting area on Plane 90°		0.422500 m <sup>2</sup>		Glare area at 76°		0.039397 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		10-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1971 lm	
LED Flux=2247lm LED Power=22W Eff=88% EfcLed=102lm/W EfcLum=90lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=36000h							
C.I.E.	21 46 73 50 100			D DIN 5040		C11	
F UTE	0.50 J + 0.50 T			B NBN		BZ 9	

50mm x 650mm



Semipiani C

180.0 ——— 0.0  
270.0 ——— 90.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %

