

Luminaire


Code 1215000A_un-ottavo
 Name ALPHABET OF LIGHT SR CIRCOLARE 350_1/8

Measurement

Code FTS24219
 Name ALPHABET OF LIGHT SR CIRCOLARE 350_1/8

Luminaire Flux	2619 lm	Luminaire Power	17.6 W	Efficacy	148.554 lm/W	Efficiency	100.00%
Source Flux	2619 lm	Maximum value	163.39 cd/klm	Position	C=25.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1366 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1366 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.068300 m ²		Emitting area on Plane 180°		0.068300 m ²	
Emitting area on Plane 0°		0.068300 m ²		Emitting area on Plane 270°		0.002500 m ²	
Emitting area on Plane 90°		0.002500 m ²		Glare area at 76°		0.082794 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		05-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2619 lm	
LED Flux=3312lm LED Power=18W Eff=79% EfcLed=188lm/W EfcLum=149lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h							
C.I.E.	33 60 82 72 100			D DIN 5040		B21	
F UTE	0.72 H + 0.28 T			B NBN		BZ 6	

1366mm x 50mm



Semipiani C

180.0 ——— 0.0
 270.0 ——— 90.0

ULOR 27.50 %
 DLOR 72.50 %
 RN 27.50 %

