

## Luminaire


Code 1304000A  
Name ALPHABET OF LIGHT C/W LINEARE 120

## Measurem.

Code FTS1701418-A  
Name ALPHABET OF LIGHT C/W LINEARE 120

Luminaire Flux	3484 lm	Luminaire Power	26.0 W	Efficacy	134.000 lm/W	Efficiency	100.00%
Source Flux	3484 lm	Maximum value	158.36 cd/klm	Position	C=45.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1200 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1200 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.060000 m2		Emitting area on Plane 180°		0.060000 m2	
Emitting area on Plane 0°		0.060000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°		0.002500 m2		Glare area at 76°		0.072733 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		24-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3484 lm	
LED Flux=4301lm LED Power=23W Eff=81% EfcLed=187lm/W EfcLum=134lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h							
C.I.E.	33 60 83 69 100			D DIN 5040	B21		
F UTE	0.69 H + 0.31 T			B NBN	BZ 6		

1200mm x 50mm



Semipiani C

180.0 ——— 0.0  
270.0 ——— 90.0

ULOR 30.60 %  
DLOR 69.40 %  
RN 30.60 %

