

Luminaire

Code AQ48301
Name A.24 SOSP. DIR+IND SHARP 2700K FL 2352WHT

Measurement

Code FTS1802332-C
Name A.24 SOSP. DIR+IND SHARP 2700K FL 2352WHT

Luminaire Flux	6619 lm	Luminaire Power	74.0 W	Efficacy	89.446 lm/W	Efficiency	100.00%
Source Flux	6619 lm	Maximum value	1374.70 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2352 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	516 mm	Width	12 mm	Height	0 mm
Horizontal Luminous Area		0.006192 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.001498 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6619 lm	


LED Flux=8664lm LED Power=65W Eff=76% EfcLed=134lm/W EfcLum=89lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=102000h

C.I.E. 98 100 100 49 100
F UTE --

D DIN 5040
B NBN

C62
BZ 1

2352mm x 27mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 51.15 %
DLOR 48.85 %
RN 51.15 %

