

Luminaire

Code BZ02804+BZ06101
 Name A.39 S/C SHARP REFR.DIR 2368 830 DALINRO + KIT LOUVRES 2368 BCO

Measurement

Code FTS2102049-A
 Name A.39 S/C SHARP REFR.DIR 2368 830 DALINRO + KIT LOUVRES 2368 BCO

| | | | | | | | |
|----------------------------|----------|-----------------|----------------|-----------------------------|--------------------|------------|--------------------|
| Luminaire Flux | 10088 lm | Luminaire Power | 70.0 W | Efficacy | 144.114 lm/W | Efficiency | 100.00% |
| Source Flux | 10088 lm | Maximum value | 1075.90 cd/klm | Position | C=80.00 G=1.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 2368 mm | Width | 45 mm | Height | 85 mm |
| Rectangular Luminous Area | | Length | 2363 mm | Width | 35 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.082705 m2 | | Emitting area on Plane 180° | 0.000000 m2 | | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | 0.000000 m2 | | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | 0.020008 m2 | | |
| Coordinate system | | CG | | Symmetry Type | Double Symmetrical | | |
| Date | | 02-11-2023 | | Maximum Gamma Angle | 180 | | |
| Measurement Distance | | 0.00 | | Measurement Flux | 10088 lm | | |


LED Flux=11146lm LED Power=62W Eff=91% EfcLed=179lm/W EfcLum=144lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h

C.I.E. 93 97 99 100 100
 F UTE 1.00 A

D DIN 5040
 B NBN

A60
 BZ 1

2368mm x 45mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %

