

## Luminaire

Code BZ04804IN0+BZ05901  
 Name A.39 S SHARP REFR.D+I 1184 WIN DALINRO + A.39 S/C SHARP REFR KIT LOUVRES 1184 BCO

## Measurement

Code FTS2103061-A  
 Name A.39 S SHARP REFR.D+I 1184 WIN DALINRO + A.39 S/C SHARP REFR KIT LOUVRES 1184 BCO


Luminaire Flux	6900 lm	Luminaire Power	58.0 W	Efficacy	118.967 lm/W	Efficiency	100.00%
Source Flux	6900 lm	Maximum value	784.48 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	1180 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.041300 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.009991 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-05-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6900 lm	

LED Flux=7804lm LED Power=52W Eff=88% EfcLed=151lm/W EfcLum=119lm/W CCT=5000K Ra=90 SDCM=3 L70(9K)=50000h

C.I.E. 98 100 100 67 100  
 F UTE --

D DIN 5040 B61  
 B NBN BZ 1

1184mm x 45mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 32.86 %

DLOR 67.14 %

RN 32.86 %

