

## Luminaire

Code CA12001+AP91300  
 Name GOPLE 80 SPOT TRK16 48V SP 4000K BCO + VECTOR 55 - SOFT FILTER

## Measurem.

Code FTS2200062  
 Name GOPLE 80 SPOT TRK16 48V SP 4000K BCO + VECTOR 55 - SOFT FILTER

Luminaire Flux	1249 lm	Luminaire Power	23.0 W	Efficacy	54.287 lm/W	Efficiency	100.00%
Source Flux	1249 lm	Maximum value	4480.84 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	77 mm	Height	150 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000402 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		01-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1249 lm	
LED Flux=2473lm LED Power=22W Eff=50% EfcLed=114lm/W EfcLum=54lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	98 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Diam=77mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



## Luminaire

Code CA12001+AP91300  
Name GOPLE 80 SPOT TRK16 48V SP 4000K BCO + VECTOR 55 - SOFT FILTER

## Measurerm.


Code FTS2200062  
Name GOPLE 80 SPOT TRK16 48V SP 4000K BCO + VECTOR 55 - SOFT FILTER

Luminaire Flux	1249 lm	Luminaire Power	23.0 W	Efficacy	54.287 lm/W	Efficiency	100.00%
Source Flux	1249 lm	Maximum value	4480.84 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	77 mm	Height	150 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000402 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		01-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1249 lm	
LED Flux=2473lm LED Power=22W Eff=50% EfcLed=114lm/W EfcLum=54lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	98 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.20	0.41	0.61	0.82	1.02	OC	0.20	0.41	0.61	0.82	1.02
OB	0.20	0.41	0.61	0.82	1.02	OD	0.20	0.41	0.61	0.82	1.02

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	5594.82	4856.32	1876.54	461.49	87.19	18.68	7.06	5.18	3.34	0.91
OB	5594.82	4856.32	1876.54	461.49	87.19	18.68	7.06	5.18	3.34	0.91
OC	5594.82	4856.32	1876.54	461.49	87.19	18.68	7.06	5.18	3.34	0.91
OD	5594.82	4856.32	1876.54	461.49	87.19	18.68	7.06	5.18	3.34	0.91



H[m]	D[m]	Max lux	Med lux	Alpha=11.6°+11.6°	G=0.0
1.00	0.41	5595	3486		
2.00	0.82	1399	872		
3.00	1.23	622	387		
4.00	1.64	350	218		
5.00	2.04	224	139		