

Luminaire


Code CE14405IN0+BZ07201
 Name SHARP REFRACTIVE TRIM 8 UNIT W1 WF SIL + SHARP REFRACTIVE KIT LOUVRES 2 UNIT BCO

Measurement

Code FTS2200280-A
 Name SHARP REFRACTIVE TRIM 8 UNIT W1 WF SIL + SHARP REFRACTIVE KIT LOUVRES 2 UNIT BCO

Luminaire Flux	2392 lm	Luminaire Power	16.0 W	Efficacy	149.485 lm/W	Efficiency	100.00%
Source Flux	2392 lm	Maximum value	1066.40 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	312 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	280 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.009800 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.002371 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		08-02-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2392 lm	
LED Flux=2642lm LED Power=16W Eff=91% EfcLed=165lm/W EfcLum=149lm/W CCT=5000K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	92 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

312mm x 55mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %

