

Luminaire

Code CE16001+BZ07404
 Name SHARP REFRACTIVE TRIM 16 UNIT 2700K WF BCO + SHARP REFRACTIVE KIT LOUVRES 4 UNIT NRO

Measurement

Code FTS2200286
 Name SHARP REFRACTIVE TRIM 16 UNIT 2700K WF BCO + SHARP REFRACTIVE KIT LOUVRES 4 UNIT NRO

Luminaire Flux	4021 lm	Luminaire Power	32.0 W	Efficacy	125.670 lm/W	Efficiency	100.00%
Source Flux	4021 lm	Maximum value	1156.50 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	608 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	560 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.019600 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.004742 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		04-10-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4021 lm	


LED Flux=4998lm LED Power=32W Eff=80% EfcLed=156lm/W EfcLum=126lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h

C.I.E. 98 100 100 100 100
 F UTE --

D DIN 5040
 B NBN

A60
 BZ 1

608mm x 55mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %

