

Luminaire

Code CM401104
Name A.39 MICRO REFR.2368 DIR 940 DALI NR/NR

Measurement

Code FTS2400096
Name A.39 MICRO REFR.2368 DIR 940 DALI NR/NR

Luminaire Flux	5612 lm	Luminaire Power	38.0 W	Efficacy	147.684 lm/W	Efficiency	100.00%
Source Flux	5612 lm	Maximum value	922.70 cd/klm	Position	C=70.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2176 mm	Width	34 mm	Height	0 mm
Horizontal Luminous Area		0.073984 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.017898 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		25-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5612 lm	


LED Flux=6643lm LED Power=35W Eff=84% EfcLed=190lm/W EfcLum=148lm/W CCT=4000K Ra=90 SDCM=3 L70(17k)=102000h

C.I.E. 100 100 100 100 100
F UTE --

D DIN 5040
B NBN

A60
BZ 1

2368mm x 45mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %

