


Luminaire

Code M325920
Name EVERYT 80 RD FI LED 2700K 2X22° B/B

Measurerm.

Code FTS1602706-A
Name EVERYT 80 RD FI LED 2700K 2X22° B/B

Luminaire Flux	1048 lm	Luminaire Power	10.0 W	Efficacy	104.800 lm/W	Efficiency	100.00%
Source Flux	1048 lm	Maximum value	1192.24 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	60 mm	Height	0 mm		
Horizontal Luminous Area			0.002827 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.000684 m2
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1048 lm	
LED Flux=1474lm LED Power=10W Eff=71% EfcLed=147lm/W EfcLum=105lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	79 93 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 1		



Luminaire

Code M325920
Name EVERYT 80 RD FI LED 2700K 2X22° B/B

Measurement

Code FTS1602706-A
Name EVERYT 80 RD FI LED 2700K 2X22° B/B

Luminaire Flux	1048 lm	Luminaire Power	10.0 W	Efficacy	104.800 lm/W	Efficiency	100.00%
Source Flux	1048 lm	Maximum value	1192.24 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	60 mm	Height	0 mm		
Horizontal Luminous Area		0.002827 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000684 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1048 lm	

LED Flux=1474lm LED Power=10W Eff=71% EfcLed=147lm/W EfcLum=105lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h


C.I.E. 79 93 99 100 100
F UTE 1.00 B

D DIN 5040
B NBN
A60
BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.44	0.88	1.32	1.75	2.19	OC	0.44	0.88	1.32	1.75	2.19
OB	0.44	0.88	1.32	1.75	2.19	OD	0.44	0.88	1.32	1.75	2.19

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1249.47	1201.78	932.42	573.86	286.13	124.76	74.08	43.05	21.18	5.87
OB	1249.47	1201.78	932.42	573.86	286.13	124.76	74.08	43.05	21.18	5.87
OC	1249.47	1201.78	932.42	573.86	286.13	124.76	74.08	43.05	21.18	5.87
OD	1249.47	1201.78	932.42	573.86	286.13	124.76	74.08	43.05	21.18	5.87



H[m]	D[m]	Max lux	Med lux	Alpha=23.7°+23.7°	G=0.0
1.00	0.88	1249	691		
2.00	1.75	312	173		
3.00	2.63	139	77		
4.00	3.51	78	43		
5.00	4.39	50	28		