

Luminaire


Code M327500
Name EVERYT 80 SQ FI TS LED2700K 2X9° B

Measurerm.

Code FTS1602724-A
Name EVERYT 80 SQ FI TS LED2700K 2X9° B

Luminaire Flux	1147 lm	Luminaire Power	10.0 W	Efficacy	114.700 lm/W	Efficiency	100.00%
Source Flux	1147 lm	Maximum value	3125.77 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire	Length	80 mm	Width	80 mm	Height	115 mm	
Rectangular Luminous Area	Length	60 mm	Width	60 mm	Height	0 mm	
Horizontal Luminous Area	0.003600 m2	Emitting area on Plane 180°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2	Emitting area on Plane 90°	0.000871 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical	Maximum Gamma Angle	180	Measurement Distance	1147 lm
Date	20-05-2024	Measurement Flux	1147 lm				
LED Flux=1474lm	LED Power=10W	Eff=78%	EfcLed=147lm/W	EfcLum=115lm/W	CCT=2700K	Ra=90	R9=50
			SDCM=3	L70(9k)=50000h			
C.I.E.	89 96 99 100 100	D DIN 5040	A60				
F UTE	1.00 A	B NBN	BZ 1				

80mm x 80mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code M327500
Name EVERYT 80 SQ FI TS LED2700K 2X9° B

Measurerm.

Code FTS1602724-A
Name EVERYT 80 SQ FI TS LED2700K 2X9° B

Luminaire Flux	1147 lm	Luminaire Power	10.0 W	Efficacy	114.700 lm/W	Efficiency	100.00%
Source Flux	1147 lm	Maximum value	3125.77 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	80 mm	Width	80 mm	Height	115 mm
Rectangular Luminous Area		Length	60 mm	Width	60 mm	Height	0 mm
Horizontal Luminous Area		0.003600 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000871 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1147 lm	


LED Flux=1474lm LED Power=10W Eff=78% EfcLed=147lm/W EfcLum=115lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h

C.I.E.	89 96 99 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.21	0.43	0.64	0.86	1.07	OC	0.21	0.43	0.64	0.86	1.07
OB	0.21	0.43	0.64	0.86	1.07	OD	0.21	0.43	0.64	0.86	1.07

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	3585.26	3004.78	1373.14	545.39	183.37	66.70	39.79	26.88	16.10	5.10
OB	3585.26	3004.78	1373.14	545.39	183.37	66.70	39.79	26.88	16.10	5.10
OC	3585.26	3004.78	1373.14	545.39	183.37	66.70	39.79	26.88	16.10	5.10
OD	3585.26	3004.78	1373.14	545.39	183.37	66.70	39.79	26.88	16.10	5.10



H[m]	D[m]	Max lux	Med lux	Alpha=12.1°+12.1°	G=0.0
1.00	0.43	3585	2165		
2.00	0.86	896	541		
3.00	1.29	398	241		
4.00	1.72	224	135		
5.00	2.15	143	87		