A.24 Stand-alone - Ceiling Circular - Sharping Emission - Ø 1122mm - 4000K - DALI - Brushed Silver

Carlotta de Bevilacqua



IP20 ⊕ **《《 (€** Dimmerable: +**0**-



LUMINAIRE

- Watt: **42W**

- Delivered lumens output: 3485lm

CCT: 4000KEfficiency: 81%Efficacy: 82.97lm/W

- CRI: **90**

- Dimmable Typology: Dali

Notes

 $220/240\mbox{Vac}$ $50/60\mbox{Hz}$ electronic driver included. Uses 1 DALI address. Sharping kit (louvers and covers for curved elements) has to be ordered separately.

DESCRIPTION

A.24 is a new comprehensive and flexible system to design light in space. A single profile, only 24 mm thick, can be installed in the recessed, ceiling or suspension mode to continuously follow the angles on a flat or three-dimensional surface. This profile hosts to a variety of performance options: diffused light, sharp optical units with three beam angles, or a smart magnetic track. This makes A.24 a flexible system, as well as an open platform to accommodate other products from the Architectural collection. The suspension version also features direct emission. The three solutions can be alternated to match the architecture and the room functions with utmost flexibility. The competence of Artemide is revealed by the quality of light, as well as by the ability of A.24 to freely move in space, with direct power connection points up to 14 metres apart.

PRODUCT CODE: AQ64315

FEATURES

Article Code: AQ64315Colour: Brushed SilverInstallation: Ceiling

- Series: **Architectural Indoor**

- Environment: Indoor

- design by: Carlotta de Bevilacqua

DIMENSIONS

Height: cm 5.4Diameter: cm 112Weight: cm 5.5

SOURCES INCLUDED

- Category: **Led**

- Number: 1

- Watt: 50W

- Color temperature (K): 4000K

- CRI: 90



Accessories



A.24 Stand-alone - Ceiling and Suspension Sharping Optional Accessory - For Ø 1550mm AQ94100



A.24 Stand-alone - Sharping Accessories -Sharping Kit - R=561mm - White AQ93001



A.24 Stand-alone - Sharping Accessories - Sharping Kit - R=561 mm - Black AQ93004



A.24 Stand-alone - Trimless frame to be used for recessed the power kit - Ceiling Ø1122 and Ø1500 AQ94200

