

A.24 - Suspension Magnetic Track - 90° Suspended Track Corner (on same plane) - Brushed Silver



IP20   


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

A.24 is a new comprehensive and flexible system to design light in space. A single profile, only 24 mm thick, can be installed in the recessed, ceiling or suspension mode to continuously follow the angles on a flat or three-dimensional surface. This profile hosts to a variety of performance options: diffused light, sharp optical units with three beam angles, or a smart magnetic track. This makes A.24 a flexible system, as well as an open platform to accommodate other products from the Architectural collection. The suspension version also features direct emission. The three solutions can be alternated to match the architecture and the room functions with utmost flexibility. The competence of Artemide is revealed by the quality of light, as well as by the ability of A.24 to freely move in space, with direct power connection points up to 14 metres apart.

TECHNICAL DRAWINGS



FEATURES

Article Code:	AQ49215	Series:	Indoor
Colour:	Brushed Silver		
Installation:	Ceiling, Suspension, Recessed		
Environment:	Indoor		

DIMENSIONS

Length:	cm 31.5
Width:	cm 31.5
Weight:	kg 0.7

Notes

Each linear, angle and curved elements are provided with mechanical and electrical joints and installation accessories. End caps have to be ordered separately. 1 suspension cable is also included. Depending on the driver, the product can be undimmable or dimmable DALI.


ACCESSORIES



240W Ceiling power supply kit (cable length 2,2 m) - 230VAC-48VDC - IP20 - 321x91x111H - Black - APP Compatible AQ16104APP



150W Ceiling power supply kit (cable length 2,2 m) - 230VAC-48VDC - IP20 - 321x91x111H - White - APP Compatible AQ17501APP




150W Ceiling power supply kit (cable length 2,2 m) - 230VAC-48VDC - IP20 - 321x91x111H - Black - APP Compatible AQ17504APP



240W Recessed power supply kit (cable length 2,2 m) - 230VAC-48VDC - IP20 - 396x195x112H - Black - DALI AQ15404



240W Ceiling power supply kit (cable length 2,2 m) - 230VAC-48VDC - IP20 - 321x91x111H - White - DALI AQ16101



240W Ceiling power supply kit (cable length 2,2 m) - 230VAC-48VDC - IP20 - 321x91x111H - Black - DALI AQ16104



240W Remote box power supply kit (2 connectors) - 230VAC-48VDC - IP20 - 313x243x57,5H - DALI AQ16000



240W Remote box power supply kit (2 connectors) - 230VAC-48VDC - IP20 - 313x243x57,5H - APP Compatible AQ16000APP




240W Recessed power supply kit (cable length 2,2 m) - 230VAC-48VDC - IP20 - 396x195x112H - White - APP Compatible AQ15401APP




240W Recessed power supply kit (cable length 2,2 m) - 230VAC-48VDC - IP20 - 396x195x112H - Black - APP Compatible AQ15404APP



240W Ceiling power supply kit (cable length 2,2 m) - 230VAC-48VDC - IP20 - 321x91x111H - White - APP Compatible AQ16101APP



240W Recessed power supply kit (cable length 2,2 m) - 230VAC-48VDC - IP20 - 396x195x112H - White - DALI AQ15401




240W Bare power supply + plug 230VAC-48VDC IP20 -


Undimmable (for dimmable version to be combined with "DALI-Selv interface")




A.24 - Suspension
- Insulating Spacer
- Use between
modules powered
by different power
supplies (1pcs) -
Brushed Silver
AQ49115



150W Bare power
supply + plug
230VAC-48VDC
IP20 -
Undimmable (for
dimmable version
to be combined
with "DALI-Selv
interface")
AQ18100




A.24 - Suspension
- End caps. (2pcs)
including 1
suspension cable
200H - Brushed
Silver
AQ49015




240W Ceiling
power supply kit
(cable length 2,2
m) - 230VAC-
48VDC - IP20 -
321x91x111H -
Black -
Undimmable
AQ17104




150W Ceiling
power supply kit
(cable length 2,2
m) - 230VAC-
48VDC - IP20 -
321x91x111H -
White -
Undimmable
AQ17601



150W Ceiling
power supply kit
(cable length 2,2
m) - 230VAC-
48VDC - IP20 -
321x91x111H -
Black -
Undimmable
AQ17604




150W Ceiling
power supply kit
(cable length 2,2
m) - 230VAC-
48VDC - IP20 -
321x91x111H -
White - DALI
AQ17501



150W Ceiling
power supply kit
(cable length 2,2
m) - 230VAC-
48VDC - IP20 -
321x91x111H -
Black - DALI
AQ17504



A.24 - Suspension
- Transition joint -
Use between
different typology
modules (track-
diffusing-
sharping) -
Brushed Silver
AQ49415




DALI to DALI-Selv
Interface
103x67x21H
AQ18200



240W Recessed
power supply kit
(cable length 2,2
m) - 230VAC-
48VDC - IP20 -
396x195x112H -
White -
Undimmable
AQ17401



240W Recessed
power supply kit



240W Ceiling
power supply kit

(cable length 2,2
m) - 230VAC-
48VDC - IP20 -
396x195x112H -
Black -
Undimmable
AQ17404

(cable length 2,2
m) - 230VAC-
48VDC - IP20 -
321x91x111H -
White -
Undimmable
AQ17101