


Airlite ceiling stable white Dali-Switch_17°_3000K_White

Carlotta de Bevilacqua, Paola di Arianello



IP20 Dimmerable:



LUMINAIRE

Power Supply: ***Supplied with independent power supply for LED,**

- **dimmable Dali-SwitchDim. Voltage: 220-240V. ClassII. SELV. IP20.**
- Watt: **35W**
- Voltage: **220-240V**
- Delivered lumens output: **3248lm**
- CCT: **3000K**
- Efficiency: **76%**
- Efficacy: **92.8lm/W**
- CRI: **90**

DESCRIPTION

Boasting elevated luminous flux, excellent colour rendering, energy efficiency, and a light compact design, Airlite is an innovative range of LED spotlights with exceptional photometric performance and flexibility. Thanks to an innovative heat dissipation system, air is filtered through open gaps in the die-cast aluminium body ensuring the efficiency and long life of our LED module. The hybrid optical system provides defined narrow beams, while keeping the light fixture dimensions compact.

PRODUCT CODE: - - -

FEATURES

- Article Code: - - -
- Colour: **White**
- Installation: **Projector**
- Material: **Aluminium**
- Series: **Scenarios**
- Area contract: **Hospitality, Retail, Culture**
- design by: **Carlotta de Bevilacqua, Paola di Arianello**

DIMENSIONS

- Length: **cm 20**
- Width: **cm 8.7**
- Height: **cm 19.4**
- Diameter: **cm 13.9**
- Base Width: **cm 8.7**
- Weight: **cm 1.3**
- Glow Wire Test: **850°**

SOURCES INCLUDED

- Category: **Led**
- Number: **1**
- Watt: **30W**
- Delivered lumens output: **3353lm**
- Color temperature (K): **3000K**
- CRI: **=80 (min.)**
- Color Tolerance: **MacAdam 3SDCM**
- Efficacy: **112lm/W**
- Service Life: **>50000h**

Accessories



Portaccessori
M077820



Lente per emissione ellittica
M078700



Filtro soft
M078800



Griglia frangiluce
M078400



Paraluce asimmetrico
M078500



Alette orientabili
M078600



Filtro cromatico
M078900



Filtro cromatico
M079000



Filtro cromatico
M079100