



# Alphabet of light system - Wall/Ceiling - Linear - 1800 mm - 3500K - Intermediate - Not powered

BIG - Bjarke Ingels Group



IP20   Dimmerable: 



## LUMINAIRE

- Watt: **33W**
- Delivered lumens output: **2977lm**
- CCT: **3500K**
- Efficiency: **80%**
- Efficacy: **90.21lm/W**
- CRI: **80**
- Dimmable Typology: **Push & APP,Push/DALI**

## Notes

Max 10 m for each power unit (10 m in one direction or 5 m in both directions). Ceiling rose with power supply for each group. (depending on the power supply chosen, the product could be APP Compatible). DALI dimming possible for the entire system or for groups of modules powered by the same driver.

## DESCRIPTION

Alphabet of light system is a lighting language that continues to grow with new curved elements so it can be developed with increasing freedom throughout space. It is a basic principle that generates an open system implementing just a handful of basic modules. Thanks to specific geometric proportions, these modules can be combined together to form endless lighting structures, from the most elemental to the most complex, both linear and curved. The BIG idea is combined with Artemide's optoelectronic expertise to give rise to an innovative construction principle that casts continuous and comfortable light. It is a minimal presence that conceals ultra-sophisticated optoelectronic and patented mechanical innovation as well as groundbreaking control. The system can be controlled using the Artemide App to create freedom both in geometric design and in the definition of dynamic performance levels, which can be programmed or modified in real time.

## PRODUCT CODE: 2141C10A

## FEATURES

- Article Code: **2141C10A**
- Colour: **White**
- Installation: **CeilingWall**
- Material: **Methacrylate, aluminum**
- Series: **Design Collection, Architectural Indoor**
- Environment: **Indoor**
- design by: **BIG - Bjarke Ingels Group**

## DIMENSIONS

- Length: **cm 179**

## SOURCES INCLUDED

- Category: **Led**
- Number: **1**
- Watt: **33W**
- Color Tolerance: **MacAdam 3SDCM**
- Service Life: **L80 (12K) 72000h**

## Accessories



Linear - 90° vertical UP joint (N°14)  
2264010A



Linear - 90° vertical DOWN joint (N°15)  
2265010A



Linear - linear joint (N°1)  
2250010A



Linear - curve 45° right joint (N°2)  
2251010A



Linear - curve 45° left joint (N°3)  
2252010A



Linear - curve 60° right joint (N°5)  
2253010A



Rose/Power Supply - Wall/Ceiling  
2268010A



Linear - curve 60° left joint (N°6)  
2254010A



Rose/Power Supply - Wall/Ceiling - APP Compatible  
2268010APP