

# Calipso Linear System 180 Suspension

Neil Poulton



IP20    Regulable: 

## LUMINARIA

- Potencia (W): **63W**
- Flujo Luminoso (lm): **4477lm**
- CCT: **3000K**
- Efficiency: **58%**
- Efficacy: **71.07lm/W**
- CRI: **90**
- Dimmable Typology: **Push**

## Notas

Uniform and diffuse light. In APP configurations must be only one App master module others must be DALI. The APP driver can not be controlled by DALI dimming system and viceversa.

## ESPECIFICACIONES

The unique honeycomb grill of Calipso was generated by feeding a photo of the moon into an image-based algorithm found on a seemingly extinct computer. The resulting fractal shape, an impure geometry that displays the irregular beauty of nature, is built from an organic honeycomb of different diameter tubes, seemingly arranged in a random geometry. This honeycomb characterizes the lamp both aesthetically and optically - not only is it visually pleasing, but it also provides an even and comfortable light emission. The result is a highly emotional lighting object that joins together optical and aesthetic intelligence. A product positioned perfectly half-way between home and professional use, Calipso is suited to a variety of applications - expressing Artemide's traditional approach to deliver high performance lighting with a unique and emotional expressiveness.

CÓDIGO PRODUCTO: 2015010A

## CARACTERÍSTICAS

- Código del artículo: **2015010A**
- Color: **White**
- Instalación: **Suspensión**
- Material: **Technopolymer, aluminium**
- Serie: **Design Collection, Architectural Indoor**
- Entorno de uso: **Interior**
- diseño: **Neil Poulton**

## DIMENSIONES

- Longitud: **cm 173.6**
- Ancho: **cm 7.9**
- Altura: **cm 7.2**
- Altura máxima del techo: **cm 200**

## FUENTES DE LUZ INCLUIDAS

- Categoría: **Led**
- Numero: **1**
- Potencia (W): **58,3W**
- Flujo Luminoso (lm): **7200lm**
- Temperatura de Color (K): **3000K**
- CRI: **90**
- Efficacy: **123lm/W**
- Service Life: **50000-L70**

ACCESORIOS



End caps kit (2pcs)  
2022010A



Joint 90° kit (dx/sx)  
2023010A



Intermediate linear joint  
2021010A



Power kit for suspension modules - 1 steel  
suspension cable + 1 alimentation cable  
2020010A



Connection cable - To be only used when the  
power kit is not in the end caps  
2024010A