


LineaLed 5W 3000K

Carlotta de Bevilacqua



IP65/67  



LUMINARIA

- Power Supply: **Electronic remote ballast**
- Potencia (W): **5W**
- Tensión de alimentación: **24Vdc**
- Flujo Luminoso (lm): **115lm**
- CCT: **3000K**
- Efficiency: **31%**
- Efficacy: **22.98lm/W**
- CRI: **75**

Notas

Electrical connection to the ballast by means of 100cm-long two-pole cable H05RN-F, with IP67 quick-release terminal block which is supplied with the fixture and can be housed in the recessing box.
Connect a maximum number of 16 fixtures in a continuous line

ESPECIFICACIONES

Light fixture with high-performance LED light sources.
Walk-over and drive-over recessed floor installation.
Composed by body in extruded aluminium, protection glass; provided with junction box for input/output connection. Floor recessing box in steel.
Technical features of light fixtures in compliance with EN60598-1.
Installation must be carried out by specialized personnel. Carefully follow the instructions.

CÓDIGO PRODUCTO: NL7398VSK0

CARACTERÍSTICAS

- Código del artículo: **NL7398VSK0**
- Material: **Aluminium, protection glass**
- Serie: **Architectural Outdoor**
- Área de uso: **Urban**
- diseño: **Carlotta de Bevilacqua**

DIMENSIONES

- Longitud: **cm 61.8**
- Ancho: **cm 4.7**
- Altura: **cm 9**

FUENTES DE LUZ INCLUIDAS

- Categoría: **Led**
- Numero: **1**
- Potencia (W): **5 W**
- Temperatura de Color (K): **3000 K**
- Tensión de alimentación: **24 Vdc**

ACCESORIOS

NO
IMAGE
AVAILABLE

Housing L=622mm
NL76720

NO
IMAGE
AVAILABLE

Housing end cap (pair) - 46,5 x 62,5 x 1,5mm
NL76750

NO
IMAGE
AVAILABLE

Female power connector for discontinuos connection
NL19023

NO
IMAGE
AVAILABLE

Male power connector for discontinuos
connection
NL19021

NO
IMAGE
AVAILABLE

ALIMENT. 40W 24Vdc IP67
NL62040

NO
IMAGE
AVAILABLE

CONNETTORE ALIMENTAZIONE + TAPPO
NL19052

NO
IMAGE
AVAILABLE

ALIMENT. 70W 24Vdc IP67
NL89080

NO
IMAGE
AVAILABLE

ALIMENT. 150W 24Vdc IP67
NL62880



LINEALED STAFFA GIUNZIONE C/CASSA
NL75810