


M141021 - Airlite binario stable white Blanco 3000K 17°- Dimmerable Dali

Carlotta de Bevilacqua, Paola di Arianello



IP20   Regulable:  



LUMINARIA

- Potencia (W): **35W**
- Tensión de alimentación: **220-240 V**
- Flujo Luminoso (lm): **3248lm**
- CCT: **3000K**
- Efficiency: **76%**
- Efficacy: **92.8lm/W**
- CRI: **90**

ESPECIFICACIONES

Boasting elevated luminous flux, excellent colour rendering, energy efficiency, and a light compact design, Airlite is an innovative range of LED spotlights with exceptional photometric performance and flexibility. Thanks to an innovative heat dissipation system, air is filtered through open gaps in the die-cast aluminium body ensuring the efficiency and long life of our LED module. The hybrid optical system provides defined narrow beams, while keeping the light fixture dimensions compact.

CÓDIGO PRODUCTO: - - -

CARACTERÍSTICAS

- Código del artículo: - - -
- Color: **Blanco**
- Instalación: **BinarioProyector**
- Material: **Aluminium**
- Serie: **Scenarios**
- Área de uso: **Retail**
- diseño: **Carlotta de Bevilacqua, Paola di Arianello**

DIMENSIONES

- Diámetro: **cm 13.9**
- Longitud base: **cm 20**
- Ancho base: **cm 8.7**
- Diámetro de recorte: **cm 9.9**
- Peso: **cm 1.6**

FUENTES DE LUZ INCLUIDAS

- Categoría: **Led**
- Numero: **1**
- Potencia (W): **30W**
- Flujo Luminoso (lm): **3353lm**
- Temperatura de Color (K): **3000K**
- CRI: **=80 (min.)**
- Color Tolerance: **MacAdam 3SDCM**
- Efficacy: **112lm/W**
- Service Life: **>50000h**

ACCESORIOS



Portaccessori
M077820



Lente per emissione ellittica
M078700



Filtro soft
M078800



Griglia frangiluce
M078400



Paraluce asimmetrico
M078500



Alette orientabili
M078600



Filtro cromatico
M078900



Filtro cromatico
M079000



Filtro cromatico
M079100