


Pad System Dali+Switch-Dim 4000K - White

Carlotta de Bevilacqua



IP20  Reglable: 



LUMINARIA

- Potencia (W): **39W**
- Flujo Luminoso (lm): **3499lm**
- CCT: **4000K**
- Efficiency: **81%**
- Efficacy: **89.72lm/W**
- CRI: **80**
- Dimmable Typology: **Dali**

ESPECIFICACIONES

Pad System is the result of a study on the theme of office lighting, which defines a new way of producing light where functional quality and comfort are the main values. With the innovative patented ALEF (Advanced Light Emitting Film) technology of LG, Pad System upsets the traditional optical approaches (based on reflectors and refractors) used in working environments, which allow to control light emission but, at the same time, result into a non-uniform appearance of the appliance's output surface. With ALEF, a patent derived from TV-screen backlighting systems, Pad System appears as a perfectly uniform luminous surface, capable to control emission over 60° beyond the appliance's ordinary one while ensuring high uniformity values, low luminance levels, and an UGR below 19, according to the provisions of UNI 12464 (luminance at 65° <3000 cd/m2 - average UGR < 19). The appliance's body has a very thin aluminium edge (90x20mm), which makes Pad System one of the world's slimmest technical office lighting systems. Flexibility is ensured by the joints, which allow to obtain multiple modular configurations.

CÓDIGO PRODUCTO: M3051N21

CARACTERÍSTICAS

- Código del artículo: **M3051N21**
- Color: **Blanco**
- Serie: **Architectural Indoor**
- Área de uso: **Hospitality, null, Retail, Culture, Residential**
- diseño: **Carlotta de Bevilacqua**

DIMENSIONES

- Longitud: **cm 120**
- Ancho: **cm 19**
- Altura: **cm 1.6**

FUENTES DE LUZ INCLUIDAS

- Categoría: **Led**
- Numero: **1**
- Potencia (W): **33W**
- Flujo Luminoso (lm): **4320lm**
- Temperatura de Color (K): **4000K**
- CRI: **80**
- Efficacy: **133lm/W**

ACCESORIOS



Kit driver linear connector - 1M. Occupies 1 DALI destination
M305521



Kit driver linear connector - 2M. Occupies 1 DALI destination
M305621



Kit driver linear and angular connector - 1M. + 1M.
Occupies 1 DALI destination
M305721



Kit driver linear and angular connector - 1M. +
2M. Occupies 2 DALI destinations
M305821



Kit driver linear and angular connector - 2M. + 2M.
Occupies 2 DALI destinations
M305921



PadSystem_End_Cap_White
M305220



PadSystem_L-shaped_Connector_White
M305320



PadSystem_90°_Shaped_Connector_White
M305420



Recessed kit for roses - 1/2/3/4 modules
M300900