


# Reeds IP68

Klaus Begasse



IP68 



## LUMINAIRE

- Watt: **9,5W**
- Voltage: **24V**
- Delivered lumens output: **79lm**
- CCT: **3000K**
- Efficiency: **12%**
- Efficacy: **9lm/W**
- CRI: **80**

## Notes

Electronic ballast 24Vdc supplied separately.

## DESCRIPTION

Floor light fixture with diffuse emission, with monochromatic LED light sources. Available with IP20 protection rating for indoors, IP67 and IP68 for outdoors. IP67 and IP68 versions are available in Single or Triple shape. Light is diffused through 7 PMMA rods with different heights to give the impression of a reed bed and which can be screwed to the base by means of AISI 316 stainless steel bushes. Part of the light is also diffused on the floor around the base. The base has an irregular shape, which has been designed to allow a «mosaic» connection with other light fixtures so as to create an elaborate composition as needed. Technical features in compliance with EN60598-1 (IP20, IP67) and section 2-18 (IP68). Consists of a base made up of a transparent polycarbonate casing installed between 2 AISI316 stainless steel plates fixed by means of AISI316 stainless steel screws. Water sealing is assured by a silicone gasket. The light fixture can be fastened to the floor by means of the holes in the lower plate. Technopolymer aesthetic cover. The light fixture is supplied with 24V DC power and is provided with a 5 m-long H05RN-F 2x1 cable with IP68 connector for the electrical connection to the mains suitable for 5-13.5mm diameter cables.

**PRODUCT CODE: T087500**

## FEATURES

- Article Code: **T087500**
- Colour: **Anthracite grey**
- Installation: **Floor**
- Material: **Methacrylate, polycarbonate**
- Series: **Architectural Outdoor**
- design by: **Klaus Begasse**

## DIMENSIONS

- Length: **cm 22**
- Width: **cm 22**
- Height: **cm 150**
- Impact Resistance: **IK10**
- Glow Wire Test: **750°**

## SOURCES INCLUDED

- Category: **Led**
- Number: **1**
- Watt: **9,5W**
- Color temperature (K): **3000K**
- CRI: **80**

## Accessories

NO  
IMAGE  
AVAILABLE

DRIVER 25W 24V DC  
T409996

NO  
IMAGE  
AVAILABLE

DRIVER 90W 24V DC  
T409999

NO  
IMAGE  
AVAILABLE

DRIVER 60W 24V DC  
T409998