

Tagora Ceiling 80 - Led 44° 4000K - Grey/White - Undimmable

S./R. Cornelissen



IP20 



LUMINAIRE

- Power Supply: **220/240Vac 50/60Hz electronic ballast included**
- Trasformer availability: **Integrated**
- Watt: **14W**
- Voltage: **220V-240V**
- Delivered lumens output: **1145lm**
- CCT: **4000K**
- Efficiency: **75%**
- Efficacy: **81.8lm/W**
- CRI: **90**

DESCRIPTION

Series of ceiling mounted luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. Aluminium body available in different two-coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. Tagora 80 and 270 offer a high-output spot light with aluminium optics. Tagora 270 uses a proprietary system based on a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. Tagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use high-output sources. Integrated electronic power supply, dimmable or non-dimmable options, depending on the version. Only ceiling mounted installation allowed. Compliant with standard EN60598-1 and other specific standards.

PRODUCT CODE: AB06556

FEATURES

- Article Code: **AB06556**
- Colour: **Grey/White**
- Material: **Aluminium**
- Series: **Architectural Indoor**
- design by: **S./R. Cornelissen**

DIMENSIONS

- Height: **cm 33**
- Diameter: **cm 8**
- Cutout shape: **Rounded**
- Weight: **cm 1.1**
- Glow Wire Test: **960°**

SOURCES INCLUDED

- Category: **Led**
- Number: **1**
- Watt: **14W**
- Color temperature (K): **4000K**
- CRI: **90**
- Color Tolerance: **MacAdam 3SDCM**
- Service Life: **L70 (6K) 60000h**